



This unit is a window-type current transformer (CT).
The rated primary current is 10 to 750Aac.
The rated secondary current is 5Aac.

Ordering code

WCT- **2CR** -

Code	Rated primary current (AC)	Rated secondary current (AC)	Turns of primary winding (T)	Rated ampere-turn (AT)	Rated burden (VA)	Weight (g)	Dimensions (mm)							
							A	B	C	D	E	F	G	H
010	10A	5A	10	100	5VA	600	37	70	61	61	23	70	85	57
015	15A		8	120		600	37	70	61	61	23	70	85	57
020	20A		5	100		600	37	70	61	61	23	70	85	57
025	25A		4	100		600	37	70	61	61	23	70	85	57
030	30A		4	120		600	37	70	61	61	23	70	85	57
040	40A		3	120		600	37	70	61	61	23	70	85	57
050	50A		2	100		600	37	70	61	61	23	70	85	57
060	60A		2	120		600	37	70	61	61	23	70	85	57
075	75A		2	150		600	37	70	61	61	23	70	85	57
100	100A		1	100		600	37	70	61	61	23	70	85	57
120	120A		1	120		600	37	70	61	61	23	70	85	57
150	150A		1	150		600	37	70	61	61	23	70	85	57
200	200A		1	200		600	37	70	61	61	23	70	85	57
250	250A		1	250		700	42	77	70	70	32	70	85	55
300	300A		1	300		700	42	77	70	70	32	70	85	55
400	400A		1	400		800	42	77	70	70	32	70	85	55
500	500A		1	500		600	50	93	86	86	50	85	100	57
600	600A		1	600		600	50	93	86	86	50	85	100	57
750	750A		1	750		700	50	93	86	86	50	85	100	57

Specifications

Rated frequency	50/60Hz
Accuracy	±1%
Overcurrent withstand	4000% continuous
Maximum voltage	1150V

Dimensions

