



This compact plug-in converter (isolator) receives two analog input and outputs a signal in proportion to their product or quotient.
For example, WSP-MLS/DIS can be used for the calculation of temperature correction of viscosity or density.

Features

- ★ Dielectric strength of 2000Vac between input, output and power supply
- ★ Both AC and DC power supply are available
- ★ Long operating time
- ★ Easy maintenance by plug-in structure
- ★ CE approved

Ordering code

WSP- - -

Code	Model
MLS	Multiplier
DIS	Divider

Code	Input	Input Resistance
10	0 to 10mVdc	1MΩ
11	0 to 100mVdc	1MΩ
12	0 to 1Vdc	1MΩ
13	0 to 5Vdc	1MΩ
14	1 to 5Vdc	1MΩ
15	0 to 10Vdc	1MΩ
16	0 to 50mVdc	1MΩ
17	0 to 60mVdc	1MΩ
32	0 to 1mA	50Ω
33	0 to 10mA	50Ω
34	0 to 16mA	50Ω
35	0 to 20mA	50Ω
36	4 to 20mA	50Ω
99	Contact us for other than the above	
* 1	Full Scale Range: Current input 1mA to 20mA Voltage input 10mV to 10V	

Code	Output	Allowable Load
A	4 to 20mA	750Ω or less
D	0 to 1mA Accuracy ±1.6% FS	15kΩ or less
G	0 to 20mA	750Ω or less
H	1 to 5V	2.5kΩ or more
L	0 to 1V	500Ω or more
N	0 to 5V	2.5kΩ or more
P	0 to 10V	10kΩ or more
S	Contact us for other than the above	
* 1	Current output 20mA or less Voltage output 10V or less	

Code	Test Report
X	None
T	With Test report

Code	Power Supply
A	100 to 240Vac ±10% 50/60Hz
D	24Vdc ±10%
8	100 to 120Vdc ±10%

K1 = 100
K2 = 100
* K1, K2 is the factory settings.
It can't be changed after shipment.

* 1...CE approval do not adapt input range code 99 and output range code S.

Specifications

Equation	<Multiplier> Output = (K1/100 x Input 1) x (K2/100 x Input 2) K1, K2 : Specified in the range of 0.1-100.0% (standard 100%) <Divider> Output = (K2/100 x Input 2) / (K1/100 x Input 1) But, K1/100 x Input 1 > K2/100 x Input 2 K1, K2 : Specified in the range of 0.1-100.0% (standard 100%)	
Accuracy	Multiplier : ±0.1% FS (at 23°C) Divider : ±0.2% FS (at 23°C) *99, S code depends on span	
Response time	Approx. 100ms (0 to 90%)	
Allowable load resistance	Current output 15V or less of voltage drop Voltage output Load current 2mA or less For 1V FS or less of output the current is 1mA or less	
Zero & span adjustment	±10% FS (Front switch)	
Operating temperature	-5 to +55°C	
Operating relative humidity	90% or less (non-condensing)	
Temperature coefficient	±0.015% FS of span per °C	
Isolation	Between input, output, and power supply	
Insulation resistance	100MΩ or more with a 500Vdc megger Between input, output, and power supply terminal	
Dielectric strength	2000Vac for 1 minute	
Power consumption	A : 100 to 240Vac ±10% Approx. 5.5VA D : 24Vdc ±10% Approx. 100mA 8 : 100 to 120Vdc ±10% Approx. 25mA	
Power supply variation	±0.1% FS (within the range of rated voltage)	
Dimensions	84(H) X 23(W) X 106.5(D)mm	
Weight	Approx. 150g	
Structure	Plug-in	
Connection	M3 SEMS screw part of the base socket	
Material of terminal screw	Chromated iron	
Case color and material	Ivory, heat-resistant ABS resin(94V-0)	
Applicable Directive	EN61326-1, EN61010-1, EN IEC 63000 Installation category : II, Pollution degree : 2	
Mounting	DIN rail or wall surface	

Terminal connections

No	Signal	Description
1	No.1 INPUT(+)	No.1 Input
4	No.1 INPUT(-) No.2 INPUT(-)	
5	No.2 INPUT(+)	No.2 Input
8	NC	
9	OUTPUT(+)	Output
12	OUTPUT(-)	
13	POWER U(+)	Power Supply
14	POWER V(-)	

* Specification is subject to change without notice