



Code	Rated Primary Current	Rated Secondary Voltage	Internal Resistance	Input Overcurrent	Accuracy
19	$\pm 1.999\mu\text{A}$	$\pm 199.9\text{mV}$	$100\text{k}\Omega$	$\pm 1\text{mA}$ or less	$\pm (1\% \pm 1\text{digit})$
20	$\pm 19.99\mu\text{A}$		$10\text{k}\Omega$	$\pm 5\text{mA}$ or less	$\pm (0.5\% \pm 1\text{digit})$
21	$\pm 199.9\mu\text{A}$		$1\text{k}\Omega$	$\pm 10\text{mA}$ or less	$\pm (0.2\% \pm 1\text{digit})$
22	$\pm 1.999\text{mA}$		100Ω	$\pm 50\text{mA}$ or less	
23	$\pm 19.99\text{mA}$		10Ω	$\pm 150\text{mA}$ or less	
24	$\pm 199.9\text{mA}$		1Ω	$\pm 500\text{mA}$ or less	
25	$\pm 1.999\text{A}$		0.1Ω	$\pm 3\text{A}$ or less	
26	$\pm 5.00\text{A}$	$\pm 50\text{mV}$	0.01Ω	$\pm 8\text{A}$ or less	$\pm (0.5\% \pm 1\text{digit})$

Technical drawing of the rear view of the device. Dimensions include a total width of 85mm, a central display width of 66mm, and a height of 20mm. Mounting features include two M3 taps (L1, L2) with a 14mm vertical spacing, and two 4x6mm holes. A 2-core shielded cable (300mm) is connected to the bottom. A 5mm gap is shown at the top right.