



### 【Feature】

WPS is a seamless pipe and protective pipe welded with a screw.

As Rc1 / 2 internal thread is standard, it is used in combination with a screw type temperature sensor.

### 【Special Specificaion (Option)】

◇Special thread

### 【Ordering code】

WPS —      —  —

①    ②    ③    ④    ⑤    ⑥    ⑦

Contents	Code	Specifications
Model	WPS	Pull-out protection tube, Thread type
① Outer thread type	R	Taper thread
	G	Parallel thread
② Outer thread size	15	1/2
	20	3/4
	25	1
	<input type="text"/>	Please inform for other than above
③ Thread material	UB	SUS 304
	UC	SUS 316
	Z1	Please inform for other than above
④ Protection tube dimensions	08	φ8mm (Diameter φ6mm)
	10	φ10mm (Diameter φ8mm)
	12	φ12mm (Diameter φ10mm)
	15	φ15mm (Diameter φ11mm)
	17	φ17.3mm (Diameter φ13.3mm)
	22	φ21.7mm (Diameter φ16.1mm)
	<input type="text"/>	Please inform for other than above
⑤ Protection tube material	UB	SUS304
	UC	SUS316
	Z2	Please inform for other than above
⑥ Immersion length	<input type="text"/>	Immersion length (mm)
⑦ Special	<input type="text"/>	S

※The insertion length of the temperature sensor used in combination is (insertion length of protective tube) + 20 mm.

### 【Dimensions】

